

**Sistema de conexión flexible para frascos DURAN[®] GL45**

Cierre roscado GL 45 con dos o tres orificios (rosca GL 14).

Resistente a una temperatura de máximo 140 °C.

Materiales utilizados: PP y PTFE. Esterilizables en autoclave. Sistema modular flexible. Se pueden conectar cuatro diámetros de tubo distintos (1,6 mm; 3,0 mm; 3,2 mm; y 6,0 mm). Es posible una ecualización de presión estéril mediante el uso de un filtro de membrana. Los orificios no usados se pueden tapar. Aplicaciones típicas: transporte seguro de medios líquidos en un sistema cerrado y esterilizado (se reduce la evaporación)



Code	Description	Packaging
LLG06226328	Screw cap HPLC, GL 45PP, 4 Port assembl	1 pz
LLG06226329	Replacement-Set for HPLCScrew cap	1 pz
LLG06226915	Set for pressure compensation4 Port scr	1 pz
LLG06227780	Screw cap GL 45, PP2 port GL 14	1 pz
LLG06227781	Screw cap GL 14for hose connection	1 pz
LLG06227782	Insert for screw capGL 14, 6,0 mm	1 pz
LLG06228023	Set for pressure compensation2 and 3 Po	1 pz
LLG06229494	Insert for screw capGL 14, 1,6 mm	1 pz
LLG06229495	Insert for screw capGL14, 3,0 mm	1 pz
LLG06230213	Insert for screw capGL 14, 3,2 mm	1 pz
LLG06230844	Membrane filter 0.2 µm, PTFEGL 14, for	1 pz
LLG07623018	Screw cap GL 45, PP3 port GL 14	1 pz
LLG07623838	Screw-cap GL 14red (PBT), with PTFEprot	1 pz



CARLO ERBA Reagents SA
Calle Filadors 35,
6º Planta 5º Puerta
08208 Sabadell (BCN)
Tel. +34 93 693 37 35
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
a Certified Quality
Management System*



