



Tubing Versilic, Silicone

Tubing Versilic®, Silicone

Versilic® 60 shore tubing is biologically inert and does not inhibit cell culture. It stays flexible down to -50 °C and maintains its chemical, mechanical and electrical performance up to 200 °C. Versilic® meets the European Pharmacopoeia requirements for silicone elastomer for closures and tubing, USP Class VI biological tests and ISO 10993 biocompatibility (systemic toxicity, irritation, sensitization, cytotoxicity, hemocompatibility and Ames test).



Code	Description	Packaging
LLG09205275	Tubing Versilic®, Silicone, Int. diam. 6 mm, Ext. diam. 10 mm, Wall thickness 2 mm	1 pz.
LLG09205306	Tubing Versilic®, Silicone, Int. diam. 7 mm, Ext. diam. 11 mm, Wall thickness 2 mm	1 pz.
LLG09205285	Tubing Versilic®, Silicone, Int. diam. 8 mm, Ext. diam. 12 mm, Wall thickness 2 mm	1 pz.
LLG09205307	Tubing Versilic®, Silicone, Int. diam. 9 mm, Ext. diam. 13 mm, Wall thickness 2 mm	1 pz.
LLG09205308	Tubing Versilic®, Silicone, Int. diam. 10 mm, Ext. diam. 14 mm, Wall thickness 2 mm	1 pz.
LLG09205309	Tubing Versilic®, Silicone, Int. diam. 12 mm, Ext. diam. 17 mm, Wall thickness 2.5 mm	1 pz.
LLG09205300	Tubing Versilic®, Silicone, Int. diam. 0.5 mm, Ext. diam. 2.5 mm, Wall thickness 1 mm	1 pz.
LLG09205301	Tubing Versilic®, Silicone, Int. diam. 1 mm, Ext. diam. 3 mm, Wall thickness 1 mm	1 pz.
LLG09205302	Tubing Versilic®, Silicone, Int. diam. 2 mm, Ext. diam. 4 mm, Wall thickness 1 mm	1 pz.
LLG09205303	Tubing Versilic®, Silicone, Int. diam. 3 mm, Ext. diam. 5 mm, Wall thickness 1 mm	1 pz.
LLG09205304	Tubing Versilic®, Silicone, Int. diam. 4 mm, Ext. diam. 6 mm, Wall thickness 1 mm	1 pz.
LLG09205305	Tubing Versilic®, Silicone, Int. diam. 5 mm, Ext. diam. 7 mm, Wall thickness 1 mm	1 pz.
LLG09205267	Tubing Versilic®, Silicone, Int. diam. 4 mm, Ext. diam. 8 mm, Wall thickness 2 mm	1 pz.



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*



