



Rubber Tubing, Viton

Rubber Tubing, Viton®

- Fluoroelastomer Rubber (FPM), black
- Temperature range -10 to over 200 °C
- Good resistance to ozone and weathering, as well as benzene and mineral oil
- Durometer 75 Shore A



Code	Description	Packaging
LLG09205774	Rubber Tubing, Viton®, Int. diam. 6 mm, Ext. diam. 10 mm, Wall thickness 2 mm	1 pz.
LLG09205782	Rubber Tubing, Viton®, Int. diam. 8 mm, Ext. diam. 11 mm, Wall thickness 1.5 mm	1 pz.
LLG09205784	Rubber Tubing, Viton®, Int. diam. 8 mm, Ext. diam. 12 mm, Wall thickness 2 mm	1 pz.
LLG09205787	Rubber Tubing, Viton®, Int. diam. 9 mm, Ext. diam. 13 mm, Wall thickness 2 mm	1 pz.
LLG09205792	Rubber Tubing, Viton®, Int. diam. 10 mm, Ext. diam. 14 mm, Wall thickness 2 mm	1 pz.
LLG09205745	Rubber Tubing, Viton®, Int. diam. 2 mm, Ext. diam. 4 mm, Wall thickness 1 mm	1 pz.
LLG09205758	Rubber Tubing, Viton®, Int. diam. 3 mm, Ext. diam. 5 mm, Wall thickness 1 mm	1 pz.
LLG09205765	Rubber Tubing, Viton®, Int. diam. 4 mm, Ext. diam. 6 mm, Wall thickness 1 mm	1 pz.
LLG06055794	Rubber Tubing, Viton®, Int. diam. 4 mm, Ext. diam. 7 mm, Wall thickness 1.5 mm	
LLG09205769	Rubber Tubing, Viton®, Int. diam. 5 mm, Ext. diam. 7 mm, Wall thickness 1 mm	1 pz.
LLG09205772	Rubber Tubing, Viton®, Int. diam. 6 mm, Ext. diam. 8 mm, Wall thickness 1 mm	1 pz.



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*

