

4-Position-Magnetic Stirrer LLG-uniSTIRRER 1/M4

LLG Labware

4-Position-Magnetic Stirrer LLG-uniSTIRRER 1/M4

An **Ultra-flat** inductive magnetic stirrer without heating with timer. The modern magnet coil technology consists only of non-moving parts and therefore quarantees a wear-free drive.

For a better mixing of samples it is possible to change the direction of rotation every 30 seconds.

- -Max. stirring quantity per stirring position 400 ml
- -Timer (1 to 99 min, infinitely)
- -100 % wear- and maintenance-free inductive drive
- -LED-display for an exact adjustment of the rotation speed
- -Digital regulated rotation speed
- -Alteration of the stirring direction
- -High Protection class IP 65
- -Stainless steel surface

Scope of supply: magnetic stirrer, 1 mains adapter each US, AUS, UK, 1

stirring rod 25 x 8 mm

Specifications Stirring positions:

Distance between Stirring postions:

Max. Stirring quantity (H2O): 4

95 mm

 $4 \times 0.4 I = 1.6 I$

Speed range: 15 ... 1200 min-1

Permissible ambient temperature: 5 ... 40 °C

Magnetic bar: max. 25 mm

Display: LED

Heating plate (W x D): 122 x 385 mm

Dimensions (W x D x H): 126 x 457 x 13.5 mm

Weight: 1.9 kg

Power supply: 100 ... 240 V, 50/60 Hz

IP code: IP 65 Warranty: 3 years







Code	Description	Packaging
LLG06263425	uniSTIRRER 1/M4 4-position magnetic stirrer with EU plug	1 pz
LLG06263426	uniSTIRRER 1/M4 4-position magnetic stirrer with UK plug	1 pz.



CARLO ERBA Reagents S.A.S. Chaussée du Vexin – 27106 Val de Reuil cedex

N° TVA: FR 63391048824 Tél: +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

