



Conductivity meters Seven2Go pro S7

Mettler-Toledo Online

Conductivity meters Seven2Go[®] pro S7

Portable professional model for conductivity measurement.

- New, intuitive menu structure with fast and easy T-Pad navigation
- Robust design with IP67 protection for use in harsh and demanding environments
- Intelligent Sensor Management (ISM[®]) functionality reduces the risk of errors
- New sunlight-proof screen guarantees screen readability even in direct sunlight
- New StatusLight gives a fast, visual confirmation showing if the meter is ready to measure or not
- Operating support for 12 languages with information shown in complete words and sentences
- Easy 1 point calibration with option of manual cell constant entry
- 3 predefined standards and 1 user defined standard
- Automatic, manual and time dependant endpoint recording
- Data memory storage for 2000 GLP data points with weatherproof Micro-USB connection for data export
- Power requirements: 4 x 1.5 V AA or 1.3 V NiMH accumulators

**Scope of supply:**

S7-Meter: Includes instrument, LabX direct pH, USB cable, electrode clip, base accessory, operating instructions, quick guide, test certificate, declaration of conformity, batteries

S7-Standard kit: As S7-Meter, but also with InLab 738-ISM and sachets of conductivity standard 1413 $\mu\text{S}/\text{cm}$ and 12.88 mS/cm

S7-Field kit: As S7-Standard kit, but also with bottles for calibration, uGo[®] carrying case

S7-USP/EP kit: As S7-Field kit, but with InLab 742-ISM instead of InLab 738-ISM

Specifications**Conductivity**

Measuring range:
Resolution:
Accuracy:
0.010 µS/cm ... 1000 mS/cm
0.001 ... 1 (auto-range)
±0.5 %

Temperature
Measuring range:
Resolution:
Accuracy: -5,0 ... 105 °C
0.1 °C
±0.1 °C

TDS
Measuring range:
Resolution:
Accuracy:
0.01 mg/l ... 600 g/l
0.01 ... 1 (auto-range)
±0.5 %

Specific resistance
Measuring range:
0.01 ... 100.0 MWcm

Salinity
Measuring range:
0.01 ... 42 psu

Conductivity Ash
Measuring range:
0.01 ... 2022 %

Dimensions (W x D x H): 222 x 70 x 35 mm

Code	Description	Packaging
LLG06265256	Conductivity meters Seven2Go pro S7, Type S7-Field kit	1 pz.
LLG06265254	Conductivity meters Seven2Go pro S7, Type S7-Meter	1 pz.
LLG06265255	Conductivity meters Seven2Go pro S7, Type S7-Standard kit	1 pz.
LLG06265257	Conductivity meters Seven2Go pro S7, Type S7-USP/EP kit	1 pz.





CARLO ERBA Reagents S.A.S.
Chaussée du Vexin – 27106 Val
de Reuil cedex
N° TVA: FR 63391048824
Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



*CARLO ERBA
Reagents operates with
a Certified Quality
Management System*

