

**Dissolved oxygen meter Seven2Go pro S9**

Mettler-Toledo Online

**Dissolved oxygen meter Seven2Goä pro S9**

Portable professional model for dissolved oxygen measurement.

- New, intuitive menu structure with fast and easy T-Pad navigation
- Robust design with IP67 protection for use in harsh and demanding environments
- Intelligent Sensor Management (ISM®) functionality reduces the risk of errors
- New sunlight-proof screen guarantees screen readability even in direct sunlight
- New StatusLight gives a fast, visual confirmation showing if the meter is ready to measure or not
- Operating support for 12 languages with information shown in complete words and sentence
- Up to 2 calibration points and a choice of 2 predefined oxygen standards
- Automatic, manual and time dependant endpoint recording
- Data memory storage for 2000 GLP data points with weatherproof Micro-USB connection for data export
- Power requirements: 4 x 1.5 V AA or 1.3 V NiMH accumulators

**Scope of supply:**

**S9-Meter:** Includes instrument, LabX® direct pH, USB cable, electrode clip, base accessory, operating instructions, quick guide, test certificate, declaration of conformity, batteries

**S9-Standard kit:** As S9-Meter, but also with InLab® OptiOxä, zero oxygen tablets

**S9-Field kit:** As S9-Standard kit, but also with bottles for calibration, uGoä carrying case, InLab® OptiOxä with protective guard

**S9-BOD kit:** As S9-Field kit, but including InLab® OptiOxä (without protective guard), BOD adapter, BOD application note

**Specifications**

**DO Saturation****Measuring range:****Resolution:****Accuracy:****0.1 ... 500.0%****0.1****±10%****Temperature****Measuring range:****Resolution:****Accuracy:****0.0 ... 50.0°C****0.1°C****±0.1°C****Dissolved Oxygen****Measuring range:****Resolution: 0.01 ... 50.00mg/l (ppm)****0.01****Accuracy: ± 0.1mg/l in range 0 ... 8mg/l****± 0.2mg/l in range 8 ... 20mg/l****± 10% in range 20 ... 50mg/l****Pressure****Measuring range:****Resolution:****Accuracy:****500 ... 1100mbar****1****±2%****Dimensions (W x D x H): 222 x 70 x 35mm**

Code	Description	Packaging
LLG06265266	Dissolved oxygen meter Seven2Go pro S9, Type S9-BOD kit	1 pz.
LLG06265265	Dissolved oxygen meter Seven2Go pro S9, Type S9-Field kit	1 pz.
LLG06265263	Dissolved oxygen meter Seven2Go pro S9, Type S9-Meter	1 pz.
LLG06265264	Dissolved oxygen meter Seven2Go pro S9, Type S9-Standard kit	1 pz.





CARLO ERBA Reagents S.A.S.  
Chaussée du Vexin – 27106 Val  
de Reuil cedex  
N° TVA: FR 63391048824  
Tél : +33 (0)2 32 09 20 00  
[www.carloerbareagents.com](http://www.carloerbareagents.com)



*CARLO ERBA  
Reagents operates with  
a Certified Quality  
Management System*

