

**Reciprocating shaker Promax 1020****Heidolph****Reciprocating shaker Promax 1020**

The Platform Shakers Promax is suitable for the modular Incubator 1000 and is recommended for applications which require variable temperatures.

- Set and continuously adjust the variable speed on the analog control knob, ideal for separation
 - Wide range of optional accessories and attachments for a large variety of applications.
 - An overtemperature sensor preventatively shuts off the unit in a dangerous heat-up situation, particularly valuable for you in case of continuous operation
 - The insulated drive system prevents any heat-up coming from the motor and consequently thermal damage to your sample
 - Designed with a low center of gravity which prevents gliding at high speed, even on a damp surface
 - An analog process timer allows for unattended operation. When the set time has elapsed, an acoustic alarm will sound and the operation stops
- Compact model for a medium sample throughput with an ideal motion for separatory funnels.

Specifications

Type of movement: reciprocating

Orbit: 32 mm

Speed range: 30 ... 250 rpm

Max. Load: 5 kg

Timer: 1 ... 999 min

Power consumption: 50 W

Permissible ambient temperature: 5 ... 31 °C

Permissible relative moisture: 80 %

Platform dimensions (W x D): 290 x 258 mm

Overall dimensions (W x D x H): 320 x 375 x 125 mm

Weight: 8.0 kg

Power supply: 230 V, 50/60 Hz

Protection class acc. to DIN EN 60529: IP 40



Code	Description	Packaging
LLG09839853	Shakers,with rubber mat,useful area 290x258 mm PROMAX 1020,reciprocating motion frequency 30-500 1/min	1 pz.
LLG09839802	Shakers,Promax 2020,speed 20 - 400 rpm platform 390 x 340 mm, without accessories	1 pz.



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*

