



pH meter HandyLab 600

SI Analytics

pH meter HandyLab 600

CMC (Continuous Measurement Control) visualizes whether the measuring value is within the calibration range. QSC (Quality Sensor Control) informs about the actual condition of the electrode and therefore increases operation safety. IDS Technology. The secure allocation of the calibration data to the sensor eliminates any uncertainty about the date and results of its last calibration. This saves time and money while assuring the highest confidence in your measurements. Traceability of the measuring values by the digital and automatic capture of all sensor data. Transmission of all data in csv format via USB interface to the PC. Or as an alternative, formatted transfer into Excel via MultiLabImporter (included in the delivery).

Supplied with:

HL600Versatile: pH meter Set HandyLab 600 with pH electrode A7780 IDS for general applications

HL600Food: pH meter Set HandyLab 600 with pH electrode BlueLine 21 pH IDS (with reinforcement and integrated temperature sensor) for penetration measurements in the food section.

Specifications**pH****Measuring range:****Resolution:****Accuracy:**

0.000 ... 14.000 pH

± 0.001 pH

±0.004pH

mV**Measuring range:****Resolution:****Accuracy:****Relative mV-measurement:**

± 1200.0 mV

± 0.1 mV

± 0.2mV

Temperature**Measuring range:****Resolution:****Accuracy:**

-5.0 ... 105.0 °C

± 0.1 °C

±0.2°C





CARLO ERBA Reagents S.A.S.
Chaussée du Vexin – 27106 Val
de Reuil cedex
N° TVA: FR 63391048824
Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



*CARLO ERBA
Reagents operates with
a Certified Quality
Management System*

