

**Diaphragm Vacuum Pump N 920 G****KNF****Diaphragm Vacuum Pump N 920 G**

- Application: Degassing, Gel drying, Rotary evaporation, Distillation, Centrifugal concentration
- Flow rate 1.26 m<sup>3</sup>/h / Ultimate vacuum 2 mbar abs.
- High suction speed, particularly in the low vacuum range
- Integrated rotational speed control enables pumping capacity to be easily adapted manually to process requirements
- PPS pump head combined with PTFE-coated diaphragm are ideal for aggressive/corrosive gases and vapors
- Integrated gas ballast valve

Tip: When combined with the VC 900 vacuum control unit and the connection cable, the rotational speed is controlled in accordance with the requirements of the process.

**Specifications**

**Operating pressure: 0.5 bar**

**Connectors for tube: ID10 mm**

**Permissible media and ambient temperature: 5 to 40 °C**

**10 to 40 °C**

**Pump head: PPS**

**Diaphragm: PTFE-coated**

**Valves: FFPM**

**Weight: 8.5 kg**



Code	Description	Packaging
LLG06287429	Diaphragm Vacuum Pump N 920 G, Type N 920 G, Flow rate 21 l / min	1 pz.



**CARLO ERBA Reagents S.A.S.**  
 Chaussée du Vexin – 27106 Val  
 de Reuil cedex  
 N° TVA: FR 63391048824  
 Tél : +33 (0)2 32 09 20 00  
[www.carloerbareagents.com](http://www.carloerbareagents.com)



**CARLO ERBA**  
*Reagents operates with  
 a Certified Quality  
 Management System*

