

**Reciprocating shaker HS 501 digital****IKA****Reciprocating shaker HS 501 digital**

Low-profile laboratory shaker with large platform and 15kg load capacity. With continuously adjustable speed range: 0 to 300rpm, digital display and timer. Continuous operation is guaranteed even under extreme loads. Requires accessory attachments for operation (these are not supplied). Ideally suited for flasks, measuring cylinders and particularly separating funnels. Developed for universal applications.

Specifications

Type of movement: reciprocal

Shaking diameter: 30 mm

Max. Load (with attachment): 15 kg

Motor rating input/output: 70/19 W

Speed range: 0 to 300rpm

Timer: 0 to 56 mins./continuous


Dimensions (W x D x H): 505 x 585 x 120 mm

Weight (without attachment): 26 kg

Protection class acc. to DIN EN 60529: IP 21

Supply requirements: 230 V, 50/60 Hz

Tested to DIN EN IEC 61010-1.



Code	Description	Packaging
LLG06270850	Horizontal shaker HS 501 digital without accessories, 220 - 240 V	1 pz.



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*

