

Orbital shaker KS501 digital

IKA

Orbital shaker KS501 digital

Low-profile laboratory shaker with large platform and 15kg load capacity. With continuously adjustable speed range: 0 to 300rpm, digital display and timer. Continuous operation is guaranteed even under extreme loads. Requires accessory attachments for operation (these are not supplied)

Ideally suited for vessel sizes over 250ml, e.g. round bottom flasks, erlenmeyer flasks, culture flasks, bottles etc. Developed for biological and microbiological growth tests and for production of stock solutions.

Specifications

Type of movement: orbital

Orbit: 30mm

Max. Load (incl. attachment): 15kg Motor rating input / output: 70 / 19W

Speed range: 0 to 300rpm

Timer:

Interface: 0 to 56 min. / continuous

RS 232

Dimensions (W x D x H): 505 x 585 x 120mm

Weight (without attachment): 26kg

Protection class acc. to DIN EN 60529: IP21

Supply requirements: 230V 50/60Hz

Tested to DIN EN IEC 61010-1.







Code	Description	Packaging
LLG06285448	Orbital shaker KS 501 digital without accessories	1 pz.



CARLO ERBA Reagents S.A.S. Chaussée du Vexin – 27106 Val de Reuil cedex

N° TVA: FR 63391048824 Tél: +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

