

Wireless Temperature/Humidity Logger testo Saveris 2-H1

Testo

Wireless Temperature/Humidity Logger testo Saveris 2-H1

Temperature- and humidity monitoring: with the daten logger system testo Saveris 2 climatic conditions are under control - wherever you are. All measured temperature- and humidity values of storage- or working rooms are recorded precisely and sent to the Testo-Cloud via WLAN. Here the measured values are safely stored online and can be retrieved via smartphone, tablet or PC at any time. In case of limit value violations, you are directly alarmed per e-mail or SMS (optional).

- -Plug & Play, no software is required
- -Automatic data transfer via WLAN to the Testo-Cloud
- -High data security due to double storage of all values: in the wireless data logger and in the Testo-Cloud
- -Reliable alerting
- -Flexible data access
- -Comprehensive probe selection

Scope of supply: Wireless Data Logger (WLAN) with display for measuring temperature and relative humidity, capacitive humidity sensor internally, including USB cable, wall bracket, batteries, calibration protocol

Specifications

Sensor type: NTC internal

Measuring range temperature / Accuracy: -30 ... 50 °C / \pm 0.5 °C (\pm 1 digit) Measuring range humidity / Accuracy: 0 ... 100% R.H. / \pm 2 % R.H. (\pm 1 digit)

Resolution: 0.1 °C

Dimensions: 95 x 75 x 30.5 mm Weight (including batteries): 240 g Messtakt: 5 s ... 24 h (15 min preset)

Communication cycle: 1 min ... 24h (15 min preset) Storage: 10000 measured values per channel

Power supply: 4 x AA AlMn mignon cells







| Code | Description | Packaging |
|-------------|---|-----------|
| LLG06283293 | Wireless data logger testo Saveris 2-H1 | 1 pz. |



CARLO ERBA Reagents S.A.S. Chaussée du Vexin – 27106 Val de Reuil cedex

N° TVA: FR 63391048824 Tél: +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

