

### Muffle furnaces series LT 3/11 - LT 40/11, max. 1100 °C, with lift door

### Muffle furnaces series LT 3/11 - LT 40/11, max. 1100 °C, with lift door

For daily laboratory use. Models with flap door or lift door available, for temperatures from 1100 °C to 1400 °C.

- -Dual shell housing made of textured stainless steel sheets for low external temperatures and high stability
- -Adjustable air inlet integrated in door
- -Exhaust air outlet in rear wall of furnace
- -Solid state relays provide low-noise operation
- -Optionally available with flap door (L models) that can be used as work platform or with lift door (LT models) with hot surface facing away from the operator
- -Available with the programmable controllers B 410 and C 450 with adjustable ramps and hold times (L 1/12 with R7 or 3216)
- -All insulation materials used are classified as non-carcinogenic according to TRGS 905, Class 1 or 2
- -Standard connection 220-240 V 1/N/PE 50/60 Hz

## 1100 °C and 1200 °C models

- -Ceramic heating plates with integrated heating wire, splash and exhaust protected, easy to replace
- -heating from two sides (heating from three sides for muffle furnaces with interior volumes of 24 litres and 40 litres)

# 1300 °C and 1400 °C models

- -Heating elements on support tubes for free heat radiation, short heating times and long service life
- -Heating from two sides

#### **Optional**

- -Chimney, chimney with fan or catalytic converter
- -Over-temperature limiter with adjustable cutout temperature for thermal protection class 2 in accordance with EN 60519-2 as temperature limiter to protect the furnace and load
- -Protective gas connection to purge with non-flammable protective or reaction gases (not available in combination with chimney, chimney with fan or catalytic converter)
- -Manual or automatic gas supply system
- -Process control and documentation via VCD software package for monitoring, documentation and control

Max. temperature 1100 °C. Lift door with hot surface facing away from the operator.







Code	Description	Packaging
LLG06244089	Muffle furnace LT 9/12/B410 1200°C, with lift door	1 pz



CARLO ERBA Reagents S.A.S. Chaussée du Vexin – 27106 Val de Reuil cedex

N° TVA: FR 63391048824 Tél: +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

