

**Universal drying oven LLG-uniOVEN 42 and LLG-uniOVEN 110****LLG Labware****Universal drying oven LLG-uniOVEN 42 and LLG-uniOVEN 110**

Microprocessor controlled universal drying oven with **forced convection** including two shelves. Each shelf of the uniOVEN 42 and uniOVEN 110 has a load capacity of 20 kg, the total load capacity of each unit is 50 kg. The maximum number of shelves is 7 for uniOVEN 42 and 10 for uniOVEN 110 with a distance of 40 mm between shelves.

- Quick and intuitive operation
- Microprocessor control with integrated auto-diagnostic system
- Forced convection with fan
- Digital display for time and temperature
- Timer:** 1 minute to 99.9 h and continuous
- Delayed start timer: 1 minute to 99.9 h
- Outlet for vapour exhaustion
- Acoustical and visible information for end of program
- Acoustical and optical alarm at temperature differences
- Interior made of stainless steel
- Adjustable over temperature protection at 300 °C

Scope of supply: LLG-uniOVEN incl. 2 shelves

Specifications LLG-uniOVEN 42 // LLG-uniOVEN 110

Internal volume: 42 l // 110 l

Temperature range: 50 ... 250 °C

Temperature accuracy:

Temperature uniformity: ± 1 °C (at 70 °C)

± 2 °C (at 70 °C)

Permissible ambient temperature: 5 ... 40 °C

Permissible relative moisture: 80 %, not condensing

Dimensions (W x D x H): 420 x 280 x 360 mm // 500 x 445 x 500 mm

Weight: 39 kg // 66 kg

Power supply: 230 V, 50/60 Hz

Warranty: 3 years



Code	Description	Packaging
LLG06263673	uniOVEN 42, incl. UK plug Oven with forced convection, up to 250°C, 42 litre	1 pz.
LLG06263670	uniOVEN 42 Oven with forced convection up to 250°C, 42 litre	1 pz.
LLG06263675	uniOVEN 110 Oven with forced convection, up to 250°C, 110 litre	1 pz.
LLG06263678	uniOVEN 110, incl. UK plug Oven with forced convection, up to 250°C, 110 litre	1 pz.



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*

