

Thermostatic cabinets Lovibond

Thermostatic cabinets

The incubators from Lovibond® are designed for continuous tempering for different applications, mainly for the determination of BOD, the storage of wastewater samples, and the determination of enzymatic activity. The temperature range is +2°C up to +40°C and can be regulated in steps of 0,1°C. Temperature tolerance is defined with +/- 1°C respectively +/- 0,5°C (at 20°C). Low engergy consumption due to reinforced isolation. The interior of the cabinets is equipped with sockets for connecting stirrers. There are 3 models available with standard doors from 135 to 445 litres net capacity, and 2 models with glass doors with 140 and 255 litres net capacity. Illuminated LED display with actual / setpoint display.

- -Temperature range 2 °C to 40 °C, continuously adjustable in steps of 0.1 °C
- -Low power consumption
- -Illuminated LED display of preset and current temperatures
- -Ideal for BOD determination at 20 °C
- -Power sockets inside the incubator
- -5 models in 3 sizes
- -Standard door or glass door

Specifications Coolant: R134a

Fan: Axial, delivery rate 320m3/h Power supply: 220-230V/50Hz







Code	Description	Packaging
LLG09699142	Thermostatic cabinets, Capacity 135 I, External dim. (W x D x H) 600 x 600 x 850 mm, Internal dim. (W x D x H) 513 x 441 x 704 mm, Weight 39 kg, Temp. range +2 +40 max. °C	1 pz.
LLG09699147	Thermostatic cabinets, Capacity 256 I, External dim. (W x D x H) 600 x 610 x 1640* mm, Internal dim. (W x D x H) 470 x 440 x 1452 mm, Weight 77 kg, Temp. range +2 +40 max. °C	1 pz.
LLG09699146	Thermostatic cabinets, Capacity 140 I, External dim. (W x D x H) 600 x 600 x 850* mm, Internal dim. (W x D x H) 513 x 441 x 702 mm, Weight 48 kg, Temp. range +2 +40 max. °C	1 pz.
LLG09699144	Thermostatic cabinets, Capacity 255 I, External dim. (W x D x H) 600 x 610 x 1640 mm, Internal dim. (W x D x H) 470 x 440 x 1452 mm, Weight 61 kg, Temp. range +2 +40 max. °C	1 pz.





N° TVA: FR 63391048824 Tél: +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

