



## Thermostatic cabinets

**Lovibond**

### Thermostatic cabinets

The incubators from Lovibond® are designed for continuous tempering for different applications, mainly for the determination of BOD, the storage of wastewater samples, and the determination of enzymatic activity. The temperature range is +2°C up to +40°C and can be regulated in steps of 0,1°C. Temperature tolerance is defined with +/- 1°C respectively +/- 0,5°C (at 20°C). Low energy consumption due to reinforced isolation. The interior of the cabinets is equipped with sockets for connecting stirrers. There are 3 models available with standard doors from 135 to 445 litres net capacity, and 2 models with glass doors with 140 and 255 litres net capacity. Illuminated LED display with actual / setpoint display.

- Temperature range 2 °C to 40 °C, continuously adjustable in steps of 0.1 °C
- Low power consumption
- Illuminated LED display of preset and current temperatures
- Ideal for BOD determination at 20 °C
- Power sockets inside the incubator
- 5 models in 3 sizes
- Standard door or glass door

### Specifications

**Coolant:** R134a

**Fan:** Axial, delivery rate 320m<sup>3</sup>/h

**Power supply:** 220-230V/50Hz



Code	Description	Packaging
LLG09699142	Thermostatic cabinets, Capacity 135 l, External dim. (W x D x H) 600 x 600 x 850 mm, Internal dim. (W x D x H) 513 x 441 x 704 mm, Weight 39 kg, Temp. range +2 ... +40 max. °C	1 pz
LLG09699146	Thermostatic cabinets, Capacity 140 l, External dim. (W x D x H) 600 x 600 x 850* mm, Internal dim. (W x D x H) 513 x 441 x 702 mm, Weight 48 kg, Temp. range +2 ... +40 max. °C	1 pz



**CARLO ERBA Reagents S.A.S.**  
 Chaussée du Vexin – 27106 Val  
 de Reuil cedex  
 N° TVA: FR 63391048824  
 Tél : +33 (0)2 32 09 20 00  
[www.carloerbareagents.com](http://www.carloerbareagents.com)



**CARLO ERBA**  
*Reagents operates with  
 a Certified Quality  
 Management System*

