

## **Circulation thermostat PT31**

**A.KRÜSS Optronic** 

## Circulation thermostat PT31

The PT31 circulation thermostat is equipped with high performance functions. The device is ideally suited for applications requiring a temperature range at a constant level. The robust locking mechanism of the PT31 provides a sturdy connection and ensures constant temperature control of the medium.

- -Temperature control using Peltier technology
- -Space-saving, sturdy design
- -Suitable for operation with non-flammable liquids (water or water/glycol mixture)

**Specifications** 

Temperature range: 8 ... 35 °C

**Accuracy:** 

Resolution: ±0.2 °C

0.1 °C

Pump performance:

Max. pump pressure: 20 l/h

20 mbar

Cooling power: Heating power: 20 W

20 14/

Power supply: 100 ... 240 V AC, 50/60 Hz, 1.3 A

Dimensions (W x D x H): Weight: 108 x 145 x 199 mm

1.5 kg





Code	Description	Packaging
LLG09841515	Circulation thermostat PT31, Type PT31	1 pz.



CARLO ERBA Reagents S.A.S. Chaussée du Vexin – 27106 Val de Reuil cedex

N° TVA: FR 63391048824 Tél : +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

