



## Control units bioMIXcontrol / bioMIXcontrol S for stirring drives bioMIXdrive

The powerful control units are characterized by:

- Fully encapsulated and sealed stainless steel housing, water, dust and germ-proof
- SoftStart for reliable catching / centering and safe acceleration of the stirring rod with different volumes and viscosities
- Jerk-free stirring even at low speeds
- QuickSet for quick setting of start- and maximum speed
- QuickStop-function against after-run and glass breakage, storage of last working status when turning off
- Digital display for speed setting
- Extremely robust construction and performance
- Easy to clean and maximum resistance
- 3 years warranty
- Made in Germany

Power setting (10-steps) for high power with regard to large and viscous stirring amounts and reduced power for the warming-free continuous operation of stirring drives bioMIXdrive 1, 2, 3 or 4. The model bioMIXcontrol S is also stackable.

### Specifications

**Speed: 5 ... 250 rpm**

**Stirring power: 40 W**

**Power setting: 10 ... 100 % (10 steps)**

**Weight: approx. 1.3 kg**



Code	Description	Packaging
LLG09645982	Control unit bioMixcontrol 4MS for bioMIXdrive 1 only	1 pz.
LLG09645951	Control unit bioMIXcontrol 5-250 rpm, 10-stepped	1 pz.
LLG09645981	Control unit bioMixcontrol S stapable	1 pz.



**CARLO ERBA Reagents S.A.S.**  
 Chaussée du Vexin – 27106 Val  
 de Reuil cedex  
 N° TVA: FR 63391048824  
 Tél : +33 (0)2 32 09 20 00  
[www.carloerbareagents.com](http://www.carloerbareagents.com)



**CARLO ERBA**  
*Reagents operates with  
 a Certified Quality  
 Management System*

