

Thermohygrometer testo 622

Testo

Thermohygrometer testo 622

In addition to temperature and humidity, the testo 622 also measures barometric pressure. The large, clear display indicates current readings, as well as the date and time. It thus provides all important values at a glance.

Specifications

Meas. units: Temperature: °C,°F

Humidity: % rH, td, wb

Pressure: hPa, mbar, kPa, in Hg, in H2O, psi

Meas. range: -10 to 60°C

0 to 100% rH 300 to 1200 hPa Resolution: 0.1°C

0.1% rH 0.1 hPa

Accuracy ±1 digit: ±0.4°C ±2% rH at 25°C (10 to 90% rH)

±3% rH (rest of range)

±3hPA

Display: LCD

Measuring rate: 10 secs

Alarm function: LED alarm for too low or too high temperatur and/or

humidity values
Calibration reminder
Storage temp.: -20 to 60°C
Oper. temp: -10 to 60°C
Power supply: 4 x AA
Battery life: 12 months

Dimensions (L x W x H): 185 x 105 x 36mm

Weight: 240g (without batteries)







Code	Description	Packaging
LLG09718667	Thermohygrometer testo 622, Type testo 622	1 pz.



CARLO ERBA Reagents S.A.S. Chaussée du Vexin – 27106 Val de Reuil cedex

N° TVA: FR 63391048824 Tél : +33 (0)2 32 09 20 00 www.carloerbareagents.com



CARLO ERBA Reagents operates with a Certified Quality Management System

