



Conductivity meters, SevenExcellence S700

Mettler-Toledo Online

Conductivity meters, SevenExcellence S700

Modular professional system for measurements of pH, redox potential, conductivity, salinity / TDS and ion concentration. Fits up to three modules in any composition and order, can be expanded with additional measurement parameters at any time.

- Large, high resolution 7" colour touch display (capacitive), very clear and easy to operate
- Modularity and flexibility; up to 3 measuring modules can work in parallel, expansion to 2 or 3 channels possible
- Universal communication via 2 x USB, Ethernet (LAN) and RS232
- Plain text user interface in 10 languages with menu guidance in full sentences
- OneClick operation concept to quickly start frequently used functions and preferred methods
- Storage for user methods
- Highest security and GxP support (ID protection, sophisticated user management, limits / alarms, integrated radio clock, etc.)
- Intelligent sensor management (ISM®)
- Connection of stirrer, sample changer, PC, barcode reader, keyboard, local or network printer possible
- Storage up to 20000 data sets (measurements, calibrations, methods)
- 17 predefined, 60 user-defined methods
- Calibration: 13 pre-defined and 20 user-defined standards
- uPlace electrode arm with perfect vertical movement
- Compatible with all METTLER TOLEDO electrodes (Recommended: ISM® electrodes)

**Scope of supply:**

S700-Basic: Includes instrument, 1 x conductivity expansion unit, 2 x blank expansion units, uPlace electrode holder, semi-transparent cover, operating instructions, installation and quick guide, LabX® direct pH PC software, declaration of conformity, test certificate



S700-Kit: As S700-Basic, but also with InLab® 731-ISM, guide to conductivity measurements, 2 calibration sachets for 1413 µS/cm and 12.88 mS/cm

S700-Trace: As S700-Kit but with InLab® Trace instead of InLab® 731-ISM, with Flow-Cell, without calibration sachets

Specifications Measuring range // Resolution // Accuracy

Temperature MTC/ATC: -30.0 ¼ 130.0 °C // 0.1 °C // ± 0.1 °C

Conductivity: 0.001 ¼ 999999 µS/cm // 0.001 ¼ 1 // ± 0.5%

0.001 ¼ 2000 mS/cm // 0.001 ¼ 1 // ± 0.5%

0.001 ¼ 200 S/m // 0.0001 ¼ 1 // ± 0.5%

0.001 ¼ 200000 mS/m // 0.0001 ¼ 1 // ± 0.5%

0.1 to 999999 µS/m // 0.001 to 1 // ± 0.5%

TDS: 0.001 ¼ 1000 g/l // 0.001 ¼ 1 // ± 0.5%

0.001 ¼ 999999 mg/l // 0.001 ¼ 1 // ± 0.5%

Salinity: 0.01 ¼ 80000 mg/l // 0.01 ¼ 0.1 // ± 0.5%

Resistivity: 0.01 ¼ 100.0 MW x cm // 0.0001 ¼ 1 // ± 0.5%

0.01 ¼ 999999 W x cm // 0.01 ¼ 1 // ± 0.5%

Conductivity Ash: 0.000 ¼ 2022% // 0.001 ¼ 1 // ± 0.5%

Code	Description	Packaging
LLG09704354	Conductivity meters, SevenExcellence S700, Type S700-Basic	1 pz.
LLG09704355	Conductivity meters, SevenExcellence S700, Type S700-Kit	1 pz.
LLG09704356	Conductivity meters, SevenExcellence S700, Type S700-Trace	1 pz.





CARLO ERBA Reagents S.A.S.
Chaussée du Vexin – 27106 Val
de Reuil cedex
N° TVA: FR 63391048824
Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



*CARLO ERBA
Reagents operates with
a Certified Quality
Management System*

