

**Conductivity meter SevenExcellence S470**

Mettler-Toledo Online

Conductivity meter SevenExcellence S470

Modular professional system for measurements of pH, redox potential, conductivity, salinity / TDS and ion concentration. Fits up to three modules in any composition and order, can be expanded with additional measurement parameters at any time.

- Large, high resolution 7" colour touch display (capacitive), very clear and easy to operate
- Modularity and flexibility; up to 3 measuring modules can work in parallel, expansion to 3 channels possible
- Universal communication via 2 x USB, Ethernet (LAN) and RS232
- Plain text user interface in 10 languages with menu guidance in full sentences
- OneClick operation concept to quickly start frequently used functions and preferred methods
- Storage for user methods
- Highest security and GxP support (ID protection, sophisticated user management, limits / alarms, integrated radio clock, etc.)
- Intelligent sensor management (ISM®)
- Connection of stirrer, sample changer, PC, barcode reader, keyboard, local or network printer possible
- Storage up to 20000 data sets (measurements, calibrations, methods)
- 17 predefined, 60 user-defined methods
- 5 point calibration (pH), 13 pre-defined and 20 user-defined buffer groups, incl. temperature chart
- uPlace electrode arm with perfect vertical movement
- Compatible with all METTLER TOLEDO electrodes (Recommended: ISM® electrodes)

**Scope of supply:**

S470-Basic: Includes instrument, 1 x conductivity expansion unit, 1 x pH/mV expansion unit, 1 x blank expansion unit, uPlace electrode holder, semi-transparent cover, operating instructions, installation and quick guide, LabX® direct pH



PC software, declaration of conformity, test certificate

S470-Kit: As S470-Basic but with InLab® Expert Pro-ISM, guide to pH measurements, 2 buffer sachets for pH 4.01, 7.00, 9.21 and 10.00.

S470-USP/EP: As S470-Kit but with InLab® 741-ISM instead of InLab® 731-ISM and InLab® Pure Pro-ISM instead of InLab® Expert Pro-ISM, BNC/RCA-MultiPină ISM-cable (1.2 m), without 1413 $\mu\text{S}/\text{cm}$ and 12.88 mS/cm calibration sachets

Specifications Measuring range // Resolution // Accuracy

Temperature MTC/ATC: -30.0 ... 130.0 °C // 0.1 °C // ± 0.1 °C

pH: -2.000 ... 20.000 // 0.001 / 0.01 / 0.1 // ± 0.002

mV: -2000.0 ... 2000.0 // 0.1 / 1 // ± 0.1

Rel. mV: -2000.0 ... 2000.0 // 0.1 / 1 // ± 0.1

ISFET pH: 0.000 ... 14.000 // 0.001 / 0.01 / 0.1 // ± 0.05

Conductivity: 0.001 ... 999999 $\mu\text{S}/\text{cm}$ // 0.001 ... 1 // $\pm 0.5\%$

0.001 ... 2000 mS/cm // 0.001 ... 1 // $\pm 0.5\%$

0.001 ... 200 S/m // 0.0001 ... 1 // $\pm 0.5\%$

0.001 ... 200000 mS/m // 0.0001 ... 1 // $\pm 0.5\%$

0.1 ... 999999 $\mu\text{S}/\text{m}$ // 0.001 ... 1 // $\pm 0.5\%$

TDS: 0.001 ... 1000 g/l , ppt // 0.001 ... 1 // $\pm 0.5\%$

0.001 ... 999999 mg/l , ppm // 0.001 ... 1 // $\pm 0.5\%$

Salinity: 0.01 ... 80.0 psu , ppt // 0.01 ... 0.1 // $\pm 0.5\%$

Resistivity: 0.01 ... 100.0 $\text{MW} \times \text{cm}$ // 0.0001 ... 1 // $\pm 0.5\%$

0.01 ... 999999 $\text{W} \times \text{cm}$ // 0.01 ... 1 // $\pm 0.5\%$

Conductivity Ash: 0.000 ... 2022 % // 0.001 ... 1 // $\pm 0.5\%$

Code	Description	Packaging
LLG09704361	Conductivity meter SevenExcellence S470, Type S470-Basic	
LLG09704362	Conductivity meter SevenExcellence S470, Type S470-Kit	1 pz.
LLG09704363	Conductivity meter SevenExcellence S470, Type S470-USP/EP	





CARLO ERBA Reagents S.A.S.
Chaussée du Vexin – 27106 Val
de Reuil cedex
N° TVA: FR 63391048824
Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
a Certified Quality
Management System*

