

**Overhead stirrer EUROSTAR 20 digital****IKA****Overhead stirrer EUROSTAR 20 digital**

Overhead stirrer designed for simple stirring tasks for quantities up to 15 l (H₂O). It automatically adjusts the speed through microprocessor controlled technology within the speed range of 0/30 to 2000 rpm. Safety circuits installed ensures automatic cut-off in an anti-stall or overload conditions. Continuous comparison of shaft speed to desired speed is maintained and variations are adjusted automatically. This guarantees a constant speed even with changes in viscosities of the sample.

- Digital speed display
- Infinitely adjustable speed
- Push-through agitator shafts
- Overload protection
- Short-term overload operation

Specifications

Stirring quantity max. (H₂O): 15 l

Max. viscosity: 10000 mPas

Motor rating input/output: 70 / 42 W

Speed range: 0/30 to 2000 rpm

Max. torque at stirring shaft: 20 Ncm

Display: LED

Chuck range: 0.5 to 10 mm

Dimensions (W x D x H): 86 x 208 x 248 mm

Weight: 4.4 kg

Protection class DIN EN 60529: IP 42

Power supply: 230 V, 50/60 Hz



Code	Description	Packaging
LLG09816693	Overhead stirrer EUROSTAR 20 digital, Type EUROSTAR 20 digital, Connector CH	1 pz.
LLG09816691	Overhead stirrer EUROSTAR 20 digital, Type EUROSTAR 20 digital, Connector EU	1 pz.
LLG09816692	Overhead stirrer EUROSTAR 20 digital, Type EUROSTAR 20 digital, Connector UK	1 pz.



CARLO ERBA Reagents S.A.S.
 Chaussée du Vexin – 27106 Val
 de Reuil cedex
 N° TVA: FR 63391048824
 Tél : +33 (0)2 32 09 20 00
www.carloerbareagents.com



CARLO ERBA
*Reagents operates with
 a Certified Quality
 Management System*

