

**Overhead stirrer RW 28 digital****IKA****Overhead stirrer RW 28 digital**

Powerful, mechanically controlled laboratory stirrer designed for highly viscous applications for quantities up to 80l (H<sub>2</sub>O). It is suitable for intensive mixing for use in laboratories and pilot plants. The stirrer comes equipped with a protection for overheating of the motor by means of self-locking temperature limiter. Additionally, to secure bowls, a stirring shaft protection and clamping fixture are optionally available.

- Digital speed display
- Infinitely adjustable speed in two speed ranges
- Push-through agitator shafts
- Overload protection
- Error code display
- Robust, ergonomic design
- Quiet operation
- With constant power-drive

**Specifications**

**Stirring quantity max. (H<sub>2</sub>O): 80l**

**Max. viscosity: 50000mPas**

**Motor rating input/output: 220 / 90W**

**Speed range (at 50/60 Hz):**

**Speed range I (at 50/60 Hz):**

**Speed range II (at 50/60 Hz): 60 to 1400rpm / 72 to 1680rpm**

**60 to 400rpm / 72 to 480rpm**

**240 to 1400rpm / 288 to 1680rpm**

**Max. torque at stirring shaft: 900Ncm**

**Display: LED**

**Chuck range: 1 to 10mm**

**Dimensions (W x D x H): 123 x 252 x 364mm**

**Protection class DIN EN 60529: IP 40**

**Power supply: 220-240V, / 50/60Hz**



Code	Description	Packaging
LLG09816632	Overhead stirrer RW 28 digital, Type RW 28 digital S 3, Plug type CH	1 pz.
LLG09816630	Overhead stirrer RW 28 digital, Type RW 28 digital, Plug type EU	1 pz.
LLG09816631	Overhead stirrer RW 28 digital, Type RW 28 digital S 2, Plug type UK	1 pz.



**CARLO ERBA Reagents S.A.S.**  
 Chaussée du Vexin – 27106 Val  
 de Reuil cedex  
 N° TVA: FR 63391048824  
 Tél : +33 (0)2 32 09 20 00  
[www.carloerbareagents.com](http://www.carloerbareagents.com)



**CARLO ERBA**  
*Reagents operates with  
 a Certified Quality  
 Management System*

